

## White PVC fabric 680 g/m<sup>2</sup>

Polyester fabric coated with white PVC on both sides, with acrylic lacquer on both faces. For tent roofs, side walls and gables; the 680 g/m<sup>2</sup> weight suits event marquees and frequent assembly.

### TECHNICAL CHARACTERISTICS

| PROPERTY                       | VALUE                                  | STANDARD / METHOD |
|--------------------------------|----------------------------------------|-------------------|
| Base fabric                    | Polyester                              | —                 |
| Yarn (warp × weft)             | 1100 × 1100 dtex (990 den)             | —                 |
| Construction                   | 23 × 23 threads/inch                   | —                 |
| Coating                        | PVC on both sides, white               | —                 |
| Lacquer                        | Acrylic, both sides                    | —                 |
| Weight                         | 680 g/m <sup>2</sup>                   | ISO 3801          |
| Tensile strength (warp / weft) | 260 / 250 daN/5 cm                     | EN ISO 1421       |
| Tear strength (warp / weft)    | 32 / 28 daN                            | DIN 53363         |
| Coating adhesion               | 8 daN/5 cm                             | EN ISO 2411       |
| Service temperature            | −30 °C / +70 °C                        | —                 |
| Treatments                     | UV protection and anti-mould treatment | —                 |

# T2

EN 15619

### REACTION TO FIRE

**Class T2 to EN 15619 (tested to EN 14115) — AITEX report no. 2024AN2177**

- Classification certificate issued by AITEX on 2 October 2024 (EN 15619:2014; test EN 14115:2001).
- EN 15619 classifies coated fabrics for tents from T1 (most demanding) to T4. It is not a Euroclass under EN 13501-1 and has no Euroclass equivalent.
- The class applies to the tested fabric (composition, weight and colour). A copy of the certificate is supplied with the material, and before ordering on request.

### SUPPLY

Made to measure (roofs, side walls and gables) or on the roll. Ask us for widths and lengths.

### ORDERS AND SAMPLES

- Free, no-obligation quote: tell us the fabric, colour, width and metres, or your tent dimensions.  
[www.plastold.com/en/contacto](http://www.plastold.com/en/contacto)
- Free sample book for professionals, dispatched within 48–72 working hours.  
[www.plastold.com/en/muestrario-lonas-pvc](http://www.plastold.com/en/muestrario-lonas-pvc)
- Shipping across Spain and Europe.

The values in the table are typical production values: they may vary within normal manufacturing tolerances and do not constitute a contractual specification. The fire classification is the one stated in the AITEX report cited above. Check the requirements that apply to your installation with your technician.